

## Triplex Cable Surround Data Sheet

Manufactured as standard in a LSF Zero Halogen polymeric material. Used within a single cable cleat to secure triplex cable (three single core cables which are spirally twisted together), it overcomes the twist in the cable so allowing the cable to be cleated at any point along it's length.

UK Patent GB 238 9970



Part No	Triplex Cable Range		Depth mm	Weight g
	Min dia. Mm	Max dia. Mm		
SFT26	24	28	62	67.3
SFT31	28	34	62	87.0
SFT36	33	39	62	113.4
SFT43	39	47	62	140.0
SFT51	47	55	62	212.3

This product has been tested in line with EN 50368.

**Maximum short circuit test level (within 2F Clamps), 76kA at 600mm cleat spacing**

See page 2 for Cable Cleat selection details



**THORNE &  
DERRICK**  
INTERNATIONAL

**Thorne & Derrick**  
+44 (0) 191 410 4292  
www.powerandcables.com

## Cable Cleat Selection Detail for Cleats to be used with the SFT Surround for Triplex Cable

Cable Core Outside Diameter	SFT Outside Diameter	Adaptor Type	Cleat Vulcan +	Cleat Emperor	2F + Clamp
24	56	SFT26	VRT+03	ES51-59	9
25	58	SFT26	VRT+03	ES51-59	10
26	59	SFT26	VRT+03	ES58-66	10
27	61	SFT26	VRT+04	ES58-66	10
28	63	SFT26	VRT+04	ES58-66	10
28	66	SFT31	VRT+04	ES65-73	11
29	68	SFT31	VRT+04	ES65-73	11
30	70	SFT31	VRT+05	ES65-73	11
31	72	SFT31	VRT+05	ES65-73	*
32	73.5	SFT31	VRT+05	ES73-85	*
33	75	SFT31	VRT+06	ES73-85	*
34	77	SFT31	VRT+06	ES73-85	*
33	77	SFT36	VRT+07	ES73-85	*
34	79	SFT36	VRT+07	ES73-85	*
35	80	SFT36	VRT+07	ES73-85	*
36	83	SFT36	VRT+07	ES73-85	*
37	85	SFT36	VRT+07	ES84-94	*
38	86	SFT36	VRT+07	ES84-94	*
39	87	SFT36	VRT+07	ES84-94	*
39	92	SFT43	VRT+08	ES84-94	*
40	94	SFT43	VRT+08	ES94-118	*
41	96	SFT43	VRT+08	ES94-118	*
42	98	SFT43	VRT+09	ES94-118	*
43	100	SFT43	VRT+09	ES94-118	*
44	101	SFT43	VRT+09	ES94-118	*
45	103	SFT43	VRT+10	ES94-118	*
46	104.5	SFT43	VRT+10	ES94-118	*
47	106	SFT43	VRT+10	ES94-118	*
47	107	SFT51	VRT+12	ES94-118	*
48	109	SFT51	VRT+12	ES94-118	*
49	111	SFT51	VRT+12	ES94-118	*
50	113.5	SFT51	VRT+12	ES94-118	*
51	115.5	SFT51	VRT+12	ES94-118	*
52	118	SFT51	VRT+12	ES94-118	*
53	120	SFT51	VRT+12	ES118-130	*
54	122.5	SFT51	VRT+12	ES118-130	*
55	125	SFT51	VRT+12	ES118-130	*

\* Not currently available - please contact Ellis Patents



**THORNE &  
DERRICK**  
INTERNATIONAL

**Thorne & Derrick**  
+44 (0) 191 410 4292  
www.powerandcables.com