
## **18.0 V CORDLESS HYDRAULIC CRIMPING TOOL**



AUB	- 18.0⊻	Crimping force	Dimensions mm		Battery	Weight kg	
ACTION	4.0Ah	kN	length	height	width	_ Battery Li-Ion	(with battery)
SPEED	Li-lon	132	351	369	83	18.0 V 4.0 Ah	5,9
							()

MAIN APPLICATIONS - max section mm <sup>2</sup>							
L.V. lugs and splices	Insulated terminals	"C" sleeve Connectors	H.V. lugs and splices	Alu lugs and splices			
400	240	185	400	300			

		STORAGE		
Туре	Dimensions mm	Weight kg	Supplied with the tool	Purchase separately
VALP39	520x432x126	2,6	*	_
VAL 130*	360x280xh48	3,0	—	*

\*Suitable for the storage of accessories for crimping Aluminium connectors

## The tool is supplied as:

- Basic tool with battery and shoulder strap
- Spare battery
- Battery charger
- USB cable

CE

 Plastic carrying case suitable for storing the tool and 8 die sets

The next generation of Cembre cordless hydraulic tools represents a significantly advantageous evolution from current models.

Born of the renowned B135-UC type crimping tool, B1350-UCE will accept the accessories for performing the "Deep Stepped Indent" system of crimping on Aluminium cables.

The B1350-UCE will accept all semi-circular slotted dies, common to most 12 tons tools (U dies).

New Li-lon 18 V 4 Ah batteries offer a higher capacity than 14.4 V 3 Ah, while greater crimping



speed and crimping force result from a revitalised hydraulic system with double speed action: a rapid approach of the dies to the connector then a slower, more powerful speed for crimping.

A maximum pressure sensor and pressure relief valve assure greater precision and repeatability of the pressure cycle and double the provision for operator safety.

The OLED display provides essential real time tool operating information

data including:
Crimping pressure and force being generated, for confirmation of adherence to norms and best practice

VAL 130

- Battery power availability
- Tool identification, LED work light state, reset, no. of operational and service crimping cycles
- Tool service required to maintain optimum condition.

Designed with improved balance, B1350-UCE is easily manageable

Multifunction OLED display with touch button during the crimping process and, by the use of bi-component plastics, has a shell with high resistance to wear and damage.

B 1350-UCE

Rubber grip inserts, low noise and minimal vibration aid operator comfort while additional convenience and safety are provided by LED lighting of the working area.

Crimping cycle data (up to 200,000 events) is automatically stored on a memory card for transfer to PC by USB interface.

Operating temperature: -15 to +50 ° C



LED lighting of the working area

Anatomically shaped grip for improved comfort







Slot-in battery with release button

