## 18.0 V CORDLESS HYDRAULIC CRIMPING TOOL



## general features

New



Crimping force		Dimensions mm			Battery	Weight kg
	k <b>N</b>	length	height	width	Li-lon'	Weight kg (with battery)
(	35	354	133	81	18.0 V 2.0 Ah	2,19

MAIN APPLICATIONS - max section mm²							
L.V. lugs and splices	"C" sleeve Connectors	H.V. lugs and splices					
150	35	70					

	STORAGE								
	Туре	Dimensions mm	Weight kg	Supplied with the tool	Purchase separately				
V	/AL P22	465x315xh116	1,5	*	_				

## The tool is supplied as:

- Basic tool with battery and wrist strap
- Spare battery
- Battery charger

 Plastic carrying case suitable for storing the tool and accessories



Can be operated with one hand. Balanced for greater control. Head rotates 180° for ease of operation in confined spaces.

Fitted with a maximum pressure valve.

Extremely quiet, minimal vibration.

Durable moulded body offering high resistance to wear and damage in all operating conditions.

New Li-lon 18.0V 2.0Ah High Power battery.

The battery is equipped with LED indicators to show the remaining battery life at any time by pressing the adjacent button.

Supplied in a robust plastic case to accommodate the tool and all the accessories.

Two batteries and charger included.

B35-45MDE accepts many of the dies common to 45 kN Cembre crimping tools.

**B 35-45MDE** 

B35-45MDE specific dies avaiable for crimping 120 mm² and 150 mm²

Application field as shown in the table above. For further details please refer to tables of page 178-190. Operating temperature:

-15 to +50 ° C





Motor ventilation



Head rotates 180° for ease of operation



Pressure release button



Sculptured body for optimum comfort

