18.0 V CORDLESS HYDRAULIC CRIMPING TOOL

CE

18.0V	Crimping	Dimensions mm			Battery	Weight kg	
2.0Ah	force kN	length	height	width	Li-lon	(with battery)	
Li-Ion	54	458	133	81	18.0 V 2.0 Ah	2,95	

MAIN APPLICATIONS - max section AWG				
Copper lugs and splices	Aluminum lugs and splices	Aluminum H taps		
300 MCM	4/0	4/0-4/0		

STORAGE					
Туре	Dimensions mm	Weight kg	Supplied with the tool	Purchase separately	
VAL P45	497x370x137	2,3	*	-	
VAL MAT-W	175x96x45	0,93		*	

The tool is supplied as:

- Basic tool with battery
- and wrist strap
- Spare battery
- Battery charger
- Plastic carrying case suitable for storing the tool and accessories

VAL MAT-W



Available as optional accessories: VAL MAT-W metal case for storing 12 Index die sets, fits into VAL-P45.

CDD6 jaws

With "D3" groove to accept all "W" style crimping dies + "BG" fixed groove.

CDD6-8 jaws

With "D3" groove to accept all "W" style crimping dies + "O" fixed groove.

CMB1 jaws

Cutting jaws for: one-time disposable lock hasps, 4AWG Alumoweld; ACSR 4/0

CMB2 jaws

- Cutting jaws for:
- # 8 Copperweld 4/0 Cu.
- 336 MCM Aluminium
- 477 MCM ACSR (Str. 26/7)

CMB3 jaws

Cutting jaws for: - 1/4" Guy Wire - 5/16" Guy Wire

The professional tool ideal for OH lines and residential service applications.

general features

Stick tool shape for better handl Can be operated with one hand Balanced for greater control. Jaws rotate by 180° for ease of eration in confined spaces.

The tool is fitted with a maxim pressure valve.

Extremely quiet, minimal vibratic Durable moulded body offering I resistance to wear and damage all operating conditions. New Li-Ion 18V 2Ah High Pov

battery.

The battery is equipped with indicators to show the remain battery life at any time by press the adjacent button.

Supplied in a robust plastic case storing the tool and all accessor Two batteries and charger include Standard interchangeable crimp ing jaw: CDD6 with "D3" groove to accept all "W" style crimping dies + "BG" fixed groove. Operating temperature: -15 à +50 °C

B 54IVID-D6E	
The second secon	
ling. L. New	
f op-	
num	
on. high _{pe in}	
ower SEW	
sing	
e for ries.	
led.	
e	
g at	

INTERCHANGEABLE CRIMPING JAWS				
CAT. No	GROOVES	CRIMPING DIE COMPATIBILIT		
CDD6	"D3" TO ACCEPT ALL "W" STYLE CRIMPING DIES + "BG" FIXED GROOVE	FCI Burndy Green lee Ilsco	W, X Series KD6 Series ND Series	
CDD6-8	"D3" TO ACCEPT ALL "W" STYLE CRIMPING DIES + "O" FIXED GROOVE	Huskie Panduit	HT-58 Series CD-2001 series	
CMB1	Cutting jaws for: one-time disposable lock hasps; 4AVVG Alumoweld; ACSR 4/0			
CMB2	Cutting jaws for: # 8 Copperweld; 4/0 Cu.; 336 MCM Aluminium; 477 MCM ACSR (Str. 26/7)			
CMB3	Cutting jaws for: 1/4" Guy Wire ; 5/16" Guy Wire			

Canvas Bag 013

Sturdy canvas bag, suitable for storing the cutting jaws



Jaws rotate 180°



Detail of the quick jaw change device.

