



**A2**

**A2 Single Seal Industrial Cable Gland**

For all types of Unarmoured & Braid Armoured Cables

- High quality durable materials
- Robust, heavy duty design
- Displacement type seal
- Deluge protected
- -60°C to +130°C (standard), -20°C to 200°C (Thermin option page 91)

**TECHNICAL DATA**

<b>Design Specification</b>	BS 6121:Part 1:1989, IEC 62444, EN 62444
<b>Mechanical Classifications*</b>	Impact = Level 8, Retention = Class B
<b>Enclosure Protection</b>	IK10 to IEC 62262 (20 joules) Brass & Stainless Steel only
<b>CSA Certificate</b>	1211841
<b>Code of Protection</b>	Enclosure Type 4X
<b>RoK Permit For Use</b>	19-02-UL-1957
<b>Marine Approvals</b>	LRS: 01/00171 (E1), ABS: 16-LD1472056-PDA
<b>Ingress Protection Rating</b>	IP66, IP67 & IP68**
<b>Deluge Protection Compliance</b>	DTS01 : 91
<b>Cable Gland Material</b>	Brass, Electroless Nickel Plated Brass, Stainless Steel, Aluminium
<b>Seal Material</b>	CMP Thermoset Rubber
<b>Cable Type</b>	Unarmoured & Braided when terminated inside enclosure
<b>Sealing Technique</b>	CMP Unique Displacement Seal Concept
<b>Sealing Area(s)</b>	Cable Outer Sheath



\* Mechanical & Electrical Classifications applied as per IEC 62444 & EN 62444  
 \*\* Refer to page 7 or www.cmp-products.com for further information on Ingress Protection Ratings

**Cable Gland Selection Table**

Refer to illustration at the top of the page.

Cable Gland Size	Available Entry Threads "C" (Alternate Thread Lengths Available)		Overall Cable Diameter "A"		Across Flats "D"	Across Corners "D"	Protrusion Length "F"	Combined Ordering Reference (*Brass Metric)			Shroud	Cable Gland Weight (Kgs)
	Metric	Thread Length "E"	Min	Max	Max	Max		Size	Type	Ordering Suffix		
20s16	M20	10.0	3.2	8.7	24.0	26.4	25.1	20S16	A2	1RA	PVC04	0.070
20S	M20	10.0	6.1	11.7	24.0	26.4	25.1	20S	A2	1RA	PVC04	0.060
20	M20	10.0	6.5	14.0	27.0	29.7	27.2	20	A2	1RA	PVC05	0.070
25	M25	10.0	11.1	20.0	36.0	39.6	35.5	25	A2	1RA	PVC09	0.130
32	M32	10.0	17.0	26.3	41.0	45.1	34.2	32	A2	1RA	PVC10	0.150
40	M40	15.0	23.5	32.2	50.0	55.0	35.1	40	A2	1RA	PVC13	0.200
50S	M50	15.0	31.0	38.2	55.0	60.5	32.0	50S	A2	1RA	PVC15	0.260
50	M50	15.0	35.6	44.0	60.0	66.0	36.3	50	A2	1RA	PVC18	0.270
63S	M63	15.0	41.5	49.9	70.5	77.6	33.5	63S	A2	1RA	PVC21	0.430
63	M63	15.0	47.2	55.9	75.0	82.5	35.8	63	A2	1RA	PVC23	0.460
75S	M75	15.0	54.0	61.9	84.0	92.4	34.2	75S	A2	1RA	PVC26	0.520
75	M75	15.0	61.1	67.9	84.0	92.4	40.6	75	A2	1RA	PVC26	0.500
90	M90	24.0	66.6	79.9	108.0	118.8	58.3	90	A2	1RA	PVC31	1.600
100	M100	24.0	76.0	91.0	123.0	135.3	55.2	100	A2	1RA	LSF33	1.780
115	M115	24.0	86.0	97.9	133.4	146.7	65.2	115	A2	1RA	LSF34	2.670
130	M130	24.0	97.0	114.9	152.4	167.6	73.9	130	A2	1RA	LSF35	3.800

\*For material options add the following suffix to the Ordering Reference; Brass (no suffix required); Nickel Plated Brass 'S'; 316 Grade Stainless Steel '4'; Copper Free Aluminium '1'

Examples: 20A21RA5 = Nickel Plated Brass M20

Dimensions are displayed in millimetres unless otherwise stated



**THORNE & DERRICK INTERNATIONAL**

**Thorne & Derrick**  
 +44 (0) 191 410 4292  
 www.powerandcables.com