

DE TYPE - DOUBLE EYE CABLE GRIP



Ideal for pulling light to medium loads; the main advantage over the single eye cable grip is the cable being pulled can be passed through the grip, several cable grips can be used to support over a calculated distance.

Slingco Part No	Range		Lattice Weave	Lattice Length		Overall Length		Approx. Break Load	
	in	mm		in	mm	in	mm	lb	kg
DOUBLE EYE STANDARD GRIP - GALVANISED									
ZCS0305	0.25 - 0.50	10-13	Single	9	230	12	305	1,680	760
ZCS0306	0.50 - 0.75	13-19	Single	14	355	17	430	2,240	1,015
ZCS0307	0.75 - 1.00	19-25	Single	16	405	20	510	5,600	2,540
ZCS0308	1.00 - 1.50	25-38	Single	18	455	24	610	7,840	3,555
ZCS0309	1.50 - 2.00	38-50	Double	21	535	29	735	11,200	5,080
ZCS0310	2.00 - 2.50	50-63	Double	24	610	34	865	11,200	5,080
ZCS0311	2.50 - 3.50	63-89	Double	27	685	39	990	13,440	6,095
ZCS0312	3.50 - 4.50	89-115	Double	27	685	39	990	15,680	7,110
ZCS0878	4.50 - 5.50	115-140	Double	27	685	39	990	15,680	7,110
DOUBLE EYE STANDARD GRIP - 316 STAINLESS STEEL									
ZCS0823	0.25 - 0.50	10-13	Single	9	230	12	305	1,344	610
ZCS1007	0.50 - 0.75	13-19	Single	14	355	17	430	1,792	810
ZCS0931	0.75 - 1.00	19-25	Single	16	405	20	510	4,480	2,030
ZCS1265	1.00 - 1.50	25-38	Single	18	455	24	610	6,272	2,845
ZCS3995	1.14 - 1.57	29-40	Double	50	1,270	62	1,575	35,000	15,625
ZCS1252	1.50 - 2.00	38-50	Double	21	535	29	735	8,960	4,065
ZCS0319	2.00 - 2.50	50-63	Double	24	610	34	865	8,960	4,065
ZCS0213	2.50 - 3.50	63-89	Double	27	685	39	990	10,752	4,875
ZCS4873	2.50 - 3.50	63-89	Double	70	1,778	80	2,032	13,500	6,027
ZCS4596	2.50 - 3.50	63-89	Triple	56	1,422	152	3,860	16,138	7,204
ZCS0332	3.50 - 4.50	89-115	Double	27	685	39	990	12,544	5,690
ZCS1982	4.50 - 5.50	115-140	Double	27	685	39	990	12,544	5,690
ZCS4869	4.50 - 5.50	115-140	Double	70	1,778	80	2,032	13,500	6,027

OPEN ENDED CABLE GRIP



Ideal for joining two cables to form a continuous loop. Typical application: replacement of lift cables, where the old cable would be attached to the new one, and the cable then fed around with ease.

Slingco Part No	Range		Lattice Weave	Lattice Length		Approx. Break Load	
	in	mm		in	mm	lb	kg
OPEN ENDED STANDARD GRIP - GALVANISED							
ZCS0313	0.25 - 0.50	10-13	Single	15	380	1,680	760
ZCS0314	0.50 - 0.75	13-19	Single	24	610	2,240	1,015
ZCS0315	0.75 - 1.00	19-25	Single	28	710	5,600	2,540
ZCS0316	1.00 - 1.50	25-38	Single	32	815	7,840	3,555
ZCS0317	1.50 - 2.00	38-50	Double	36	915	11,200	5,080
ZCS0318	2.00 - 2.50	50-63	Double	42	1,065	11,200	5,080
ZCS1158	2.50 - 3.50	63-89	Double	48	1,220	13,440	6,095
ZCS1159	3.50 - 4.50	89-115	Double	54	1,370	15,680	7,110
ZCS1975	4.50 - 5.50	115-140	Double	54	1,370	15,680	7,110
OPEN ENDED STANDARD GRIP - 316 STAINLESS STEEL							
ZCS1995	0.25 - 0.50	10-13	Single	15	380	1,344	610
ZCS1996	0.50 - 0.75	13-19	Single	24	610	1,792	810
ZCS1997	0.75 - 1.00	19-25	Single	28	710	4,480	2,030
ZCS1998	1.00 - 1.50	25-38	Single	32	815	6,272	2,845
ZCS1999	1.50 - 2.00	38-50	Double	36	915	8,960	4,065
ZCS2000	2.00 - 2.50	50-63	Double	42	1,065	8,960	4,065
ZCS2001	2.50 - 3.50	63-89	Double	48	1,220	10,752	4,875
ZCS2002	3.50 - 4.50	89-115	Double	54	1,370	12,544	5,690
ZCS2003	4.50 - 5.50	115-140	Double	54	1,370	12,544	5,690



THORNE & DERRICK INTERNATIONAL

Thorne & Derrick
 +44 (0) 191 410 4292
 www.powerandcables.com