

DE TYPE - DOUBLE EYE CABLE GRIP



Ideal for pulling light to medium loads; the main advantage over the single eye cable grip is the cable being pulled can be passed through the grip, several cable grips can be used to support over a calculated distance.

| Slingco Part No | Range | | Lattice Weave | Lattice Length | | Overall Length | | Approx. Break Load | |
|---|-------------|---------|---------------|----------------|-------|----------------|-------|--------------------|--------|
| | in | mm | | in | mm | in | mm | lb | kg |
| DOUBLE EYE STANDARD GRIP - GALVANISED | | | | | | | | | |
| ZCS0305 | 0.25 - 0.50 | 10-13 | Single | 9 | 230 | 12 | 305 | 1,680 | 760 |
| ZCS0306 | 0.50 - 0.75 | 13-19 | Single | 14 | 355 | 17 | 430 | 2,240 | 1,015 |
| ZCS0307 | 0.75 - 1.00 | 19-25 | Single | 16 | 405 | 20 | 510 | 5,600 | 2,540 |
| ZCS0308 | 1.00 - 1.50 | 25-38 | Single | 18 | 455 | 24 | 610 | 7,840 | 3,555 |
| ZCS0309 | 1.50 - 2.00 | 38-50 | Double | 21 | 535 | 29 | 735 | 11,200 | 5,080 |
| ZCS0310 | 2.00 - 2.50 | 50-63 | Double | 24 | 610 | 34 | 865 | 11,200 | 5,080 |
| ZCS0311 | 2.50 - 3.50 | 63-89 | Double | 27 | 685 | 39 | 990 | 13,440 | 6,095 |
| ZCS0312 | 3.50 - 4.50 | 89-115 | Double | 27 | 685 | 39 | 990 | 15,680 | 7,110 |
| ZCS0878 | 4.50 - 5.50 | 115-140 | Double | 27 | 685 | 39 | 990 | 15,680 | 7,110 |
| DOUBLE EYE STANDARD GRIP - 316 STAINLESS STEEL | | | | | | | | | |
| ZCS0823 | 0.25 - 0.50 | 10-13 | Single | 9 | 230 | 12 | 305 | 1,344 | 610 |
| ZCS1007 | 0.50 - 0.75 | 13-19 | Single | 14 | 355 | 17 | 430 | 1,792 | 810 |
| ZCS0931 | 0.75 - 1.00 | 19-25 | Single | 16 | 405 | 20 | 510 | 4,480 | 2,030 |
| ZCS1265 | 1.00 - 1.50 | 25-38 | Single | 18 | 455 | 24 | 610 | 6,272 | 2,845 |
| ZCS3995 | 1.14 - 1.57 | 29-40 | Double | 50 | 1,270 | 62 | 1,575 | 35,000 | 15,625 |
| ZCS1252 | 1.50 - 2.00 | 38-50 | Double | 21 | 535 | 29 | 735 | 8,960 | 4,065 |
| ZCS0319 | 2.00 - 2.50 | 50-63 | Double | 24 | 610 | 34 | 865 | 8,960 | 4,065 |
| ZCS0213 | 2.50 - 3.50 | 63-89 | Double | 27 | 685 | 39 | 990 | 10,752 | 4,875 |
| ZCS4873 | 2.50 - 3.50 | 63-89 | Double | 70 | 1,778 | 80 | 2,032 | 13,500 | 6,027 |
| ZCS4596 | 2.50 - 3.50 | 63-89 | Triple | 56 | 1,422 | 152 | 3,860 | 16,138 | 7,204 |
| ZCS0332 | 3.50 - 4.50 | 89-115 | Double | 27 | 685 | 39 | 990 | 12,544 | 5,690 |
| ZCS1982 | 4.50 - 5.50 | 115-140 | Double | 27 | 685 | 39 | 990 | 12,544 | 5,690 |
| ZCS4869 | 4.50 - 5.50 | 115-140 | Double | 70 | 1,778 | 80 | 2,032 | 13,500 | 6,027 |

OPEN ENDED CABLE GRIP



Ideal for joining two cables to form a continuous loop. Typical application: replacement of lift cables, where the old cable would be attached to the new one, and the cable then fed around with ease.

| Slingco Part No | Range | | Lattice Weave | Lattice Length | | Approx. Break Load | |
|---|-------------|---------|---------------|----------------|-------|--------------------|-------|
| | in | mm | | in | mm | lb | kg |
| OPEN ENDED STANDARD GRIP - GALVANISED | | | | | | | |
| ZCS0313 | 0.25 - 0.50 | 10-13 | Single | 15 | 380 | 1,680 | 760 |
| ZCS0314 | 0.50 - 0.75 | 13-19 | Single | 24 | 610 | 2,240 | 1,015 |
| ZCS0315 | 0.75 - 1.00 | 19-25 | Single | 28 | 710 | 5,600 | 2,540 |
| ZCS0316 | 1.00 - 1.50 | 25-38 | Single | 32 | 815 | 7,840 | 3,555 |
| ZCS0317 | 1.50 - 2.00 | 38-50 | Double | 36 | 915 | 11,200 | 5,080 |
| ZCS0318 | 2.00 - 2.50 | 50-63 | Double | 42 | 1,065 | 11,200 | 5,080 |
| ZCS1158 | 2.50 - 3.50 | 63-89 | Double | 48 | 1,220 | 13,440 | 6,095 |
| ZCS1159 | 3.50 - 4.50 | 89-115 | Double | 54 | 1,370 | 15,680 | 7,110 |
| ZCS1975 | 4.50 - 5.50 | 115-140 | Double | 54 | 1,370 | 15,680 | 7,110 |
| OPEN ENDED STANDARD GRIP - 316 STAINLESS STEEL | | | | | | | |
| ZCS1995 | 0.25 - 0.50 | 10-13 | Single | 15 | 380 | 1,344 | 610 |
| ZCS1996 | 0.50 - 0.75 | 13-19 | Single | 24 | 610 | 1,792 | 810 |
| ZCS1997 | 0.75 - 1.00 | 19-25 | Single | 28 | 710 | 4,480 | 2,030 |
| ZCS1998 | 1.00 - 1.50 | 25-38 | Single | 32 | 815 | 6,272 | 2,845 |
| ZCS1999 | 1.50 - 2.00 | 38-50 | Double | 36 | 915 | 8,960 | 4,065 |
| ZCS2000 | 2.00 - 2.50 | 50-63 | Double | 42 | 1,065 | 8,960 | 4,065 |
| ZCS2001 | 2.50 - 3.50 | 63-89 | Double | 48 | 1,220 | 10,752 | 4,875 |
| ZCS2002 | 3.50 - 4.50 | 89-115 | Double | 54 | 1,370 | 12,544 | 5,690 |
| ZCS2003 | 4.50 - 5.50 | 115-140 | Double | 54 | 1,370 | 12,544 | 5,690 |



THORNE & DERRICK INTERNATIONAL

Thorne & Derrick
 +44 (0) 191 410 4292
 www.powerandcables.com