

**Volume 1**

**NJUG GUIDELINES ON THE POSITIONING AND COLOUR  
CODING OF UNDERGROUND UTILITIES' APPARATUS**

**PLEASE ENSURE THAT YOU READ THE LEGAL NOTICE AND DISCLAIMER  
WHICH APPEARS IN APPENDIX A OF THIS PUBLICATION**

**Issue 8: 29<sup>th</sup> October 2013**

**NJUG has a vision for street works, this vision is simply:**

- **Safety is the number one priority**
- **Utilities deliver consistent high quality**
- **Utilities work together and in partnership with local authorities and contractors to minimise disruption**
- **Utilities keep the public fully informed on all aspects of works**
- **Utilities maximise the use of sustainable methods and materials**
- **Damage to underground assets is avoided**

**This document forms part of that vision.**

**Mark Ostheimer  
Operations Director**

## NJUG Guidelines on the Positioning and Colour Coding of Underground Utilities' Apparatus

The following volumes constitute the NJUG Publications. They are living documents and may be amended from time to time. There is no attempt to describe any specific industry process as each utility has its own specifications and procedures. Not all the publications will necessarily be available at one time as individual volumes will be published when available.

<b>NJUG PUBLICATIONS</b>	
<i>Current</i>	<i>Previous</i>
<b>VOLUME 1</b>	
NJUG Guidelines on the Positioning and Colour Coding of Underground Utilities' Apparatus	NJUG 4 & 7
<b>VOLUME 2</b>	
NJUG Guidelines on the Positioning of Underground Utilities Apparatus for New Development Sites	NJUG 2, 5 & 6
<b>VOLUME 3</b>	
NJUG Guidelines on the Management of Third Party Cable Ducting	New
<b>VOLUME 4</b>	
NJUG Guidelines for the Planning, Installation and Maintenance of Utility Apparatus in Proximity to Trees	NJUG 10
<b>VOLUME 5</b>	
NJUG On-Site Environmental Good Practice Guidelines	New
<b>VOLUME 6</b>	
NJUG Guidelines on Co-ordination, Co-operation and Communication	New

The following NJUG publications have not been reviewed and have been completely withdrawn:

- NJUG 3 – Cable Locating Devices
- NJUG 8 – Performance Guide for the Assessment of Metallic Pipe and Cable Locators
- NJUG 9 – Recommendations for the Exchange of Records of Apparatus between Utilities
- NJUG 11 – Proposed Data Exchange Format for Utility Map Data
- NJUG 12 – NJUG Specification for the Digitisation of Large Scale OS Maps
- NJUG 13 – Quality Control Procedure for Large Scale OS Maps Digitised to OS 1988
- NJUG 15 – NJUG/Ordnance Survey Service Level Agreement (Technical) for Digital Map Products and Services

## NJUG Guidelines on the Positioning and Colour Coding of Underground Utilities' Apparatus

### CONTENTS

<b>Background</b>	5
<b>Scope</b>	5
<b>1. IDENTIFICATION</b>	6
1.1 Pipe / Duct Identification and Recommended Depths	6
1.2 Colour	9
1.3 Marker / Warning Systems	10
<b>2. POSITIONING OF APPARATUS IN A TWO METRE WIDE FOOTWAY</b>	10
<b>3. INSTALLING APPARATUS IN THE CARRIAGEWAY</b>	12
3.1 Specification for the Reinstatement of Openings in Highways code of practice (SROH)	12
3.2 Ducts	12
3.3 Motorways	13
<b>4. INSTALLING APPARATUS OFF THE PUBLIC HIGHWAY</b>	13
4.1 Electricity	13
4.2 Water and Waste Water	13
4.3 Communications	14
4.4 Gas	14
<b>5. FACTORS INFLUENCING THE POSITION OF UNDERGROUND APPARATUS</b>	14
<b>6. TRENCH SHARING</b>	15
<b>7. COMBINED SERVICE DUCTS, SUBWAYS AND TUNNELS</b>	16
<b>8. USE OF ABANDONED AND SURPLUS APPARATUS</b>	16
<b>9. DISTRICT HEATING</b>	16
<b>TABLE 1 – Recommended Colour Coding of Underground Utilities Apparatus</b>	7
<b>TABLE 2 – Recommended Colour Coding of Other Underground Apparatus</b>	8
<b>FIGURE 1 – Recommended Positioning of Utility Apparatus in a 2 metre footway</b>	11



The National Joint Utilities Group

## **NJUG Guidelines on the Positioning and Colour Coding of Underground Utilities' Apparatus**

<b>GLOSSARY</b>	<b>17</b>
<b>APPENDIX A</b>	
<b>Important Legal Notice and Disclaimer</b>	<b>19</b>

## **NJUG Guidelines on the Positioning and Colour Coding of Underground Utilities' Apparatus**

**These guidelines describe utility industry practice. However, it should not be assumed that all mains or services will conform to the recommendations for positioning or colour coding contained in this publication.**

This volume supersedes NJUG 4 'The Identification of Small Buried Mains and Services', NJUG 7 'Recommended Positioning of Utilities' Apparatus for New Works on New Developments and in Existing Streets' and the NJUG revision 'Utilities' Guidelines on the Positioning and Colour Coding of Apparatus'.

### **Background**

The statutory right of undertakers (utilities) to carry out works within the public highway in order to provide and maintain their apparatus dates from the mid-19th century. There are no statutory obligations governing the position or depth at which apparatus should be laid within the highway. The following guidelines should therefore be adhered to wherever practicable.

The New Roads and Street Works Act 1991, as amended by the Transport Act 2000, the Traffic Management Act 2004, the Transport (Scotland) Act 2005 together with the Street Works (Northern Ireland) Order 1995, sets down the legislative requirements to be adopted during the installation, repair and maintenance of apparatus in roads and streets.

### **Scope**

- (i) Utility apparatus can be vulnerable to damage from works carried out in the highway. The safety of operatives and the public is of paramount importance. It is therefore in the interests of all parties to make every effort to minimise both the occurrence and effect of damage (see Volume 3).
- (ii) Early consultation between highway authorities, planners, architects, developers and utilities is important to ensure that engineering and planning requirements for the installation of infrastructure are agreed.
- (iii) These guidelines apply to utility apparatus placed beneath:
  - a) Footways
  - b) Carriageways
  - c) Cycle tracks
  - d) Verges
  - e) Service strips
  - f) Footpaths

## **NJUG Guidelines on the Positioning and Colour Coding of Underground Utilities' Apparatus**

- (iv) These recommendations are based upon a two metre wide footway, which is the minimum width required to accommodate the full range of utility services. Due to the complexity of layout and size of utility and other apparatus only guidance can be given on their actual positioning. However, utilities and others should always endeavour to comply with the recommended positioning of their apparatus.
- (v) In the case of innovative street designs, such as Home Zones, the emphasis must be on early consultation between all involved to ensure that the utility services are positioned so as to allow safe access for maintenance and repair.
- (vi) On new development sites where utility apparatus is installed by the Developer or a third party, the guidelines contained within this section for the positioning and colour coding of underground apparatus should be followed. Any deviation from these guidelines should only be conducted with the agreement of the prospective asset owner. Any variation to depth of cover must permit access to all utility apparatus. For further detail see **Volume 2 – 'NJUG Guidelines on the Positioning of Underground Utilities Apparatus for New Development Sites'**.
- (vii) These guidelines include a recommended colour coding scheme facilitating the identification of apparatus within the highway in order to create a safer working environment.
- (viii) In addition to formal notification requirements specialist advice should also be obtained when works are undertaken over, under or near to the following:
  - bridges, subways, culverts, cellars, manholes, trees and railway level crossings.

In these situations the appropriate authority or asset owner should be able to offer advice and assistance.

## **1. IDENTIFICATION**



### **1.1 Pipe / Duct Identification and Recommended Depths**

Tables 1 and 2 below give the recommended industry and other underground apparatus depths and colour identification for ducts, pipes and cables.

## NJUG Guidelines on the Positioning and Colour Coding of Underground Utilities' Apparatus

**TABLE 1 – Recommended Colour Coding of Underground Utilities Apparatus**

All depths are from the surface level to the crown of the apparatus



Utility	Duct	Pipe	Cable	Marker Systems	Recommended Minimum Depths	
					Footway/Verge	Carriageway
<b>Electricity HV (High Voltage)</b>	Black or red duct or tile	N/A	Red or black	Yellow with black and red legend or concrete tiles	450-1200mm	750-1200mm
<b>Electricity LV (Low Voltage)</b>	Black or red duct or tile	N/A	Black or red	Yellow with black legend	450mm	600mm
<b>Gas</b>	Yellow	*** See row below	N/A	Black legend on PE pipes every linear metre.	600mm footway 750mm verge	750mm
<b>*** PE</b> - up to 2 bar - yellow or yellow with brown stripes (removable skin revealing white or black core pipe). - between 2 to 7 bar -orange. <b>Steel pipes</b> may have yellow wrap or black tar coating or no coating. <b>Ductile Iron</b> may have plastic wrapping <b>Asbestos &amp; Pit / Spun Cast Iron</b> – No distinguishable colour						
<b>Water non Potable &amp; Grey Water</b>	N/A	Black with green stripes	N/A	N/A	600 – 750mm	600 – 750mm
<b>Water - Firefighting</b>	N/A	Black with red stripes or bands	N/A	N/A	600 – 750mm	600 – 750mm
<b>Oil / fuel pipelines</b>	N/A	Black	N/A	Various surface markers  Marker tape or tiles above red concrete	900mm <i>All work within 3 metres of oil fuel pipelines must receive prior approval</i>	900mm <i>All work within 3 metres of oil fuel pipelines must receive prior approval</i>
<b>Sewerage</b>	Black	No distinguishing colour / material (eg: Ductile Iron may be red; PVC may be brown)	N/A	N/A	Variable	Variable
<b>Communications</b> 	Grey, white, green, Black, purple	N/A	Black or light grey	Various	250 – 350mm	450 - 600mm
<b>Water</b>	Blue or Grey	Blue polymer or blue or uncoated Iron / GRP. Blue polymer with brown stripe (removable skin revealing white or black pipe)	N/A	Blue or Blue/black	750mm	750mm minimum
<b>Water pipes for special purposes (e.g. contaminated ground)</b> 	N/A	Blue polymer with brown stripes (non-removable skin)	N/A	Blue or blue/black	750mm	750mm minimum

These guidelines describe utility industry practice. However, it should not be assumed that all apparatus will conform to the recommendations for positioning and colour coding contained in this publication.

## NJUG Guidelines on the Positioning and Colour Coding of Underground Utilities' Apparatus

**TABLE 2 – Recommended Colour Coding of Other Underground Apparatus**

All depths are from the surface level to the crown of the apparatus

Asset Owner	Duct	Pipe	Cable	Marker Systems	Recommended Minimum Depths	
					Footway	Carriageway
Highway Authority Services						
At the time of publication the following were current examples of known highway authority apparatus colour coding but local variations may occur						
Street Lighting						
England and Wales	Orange	N/A	Black	Yellow with black legend	450mm	600mm
Scotland	Purple	N/A	Purple	Yellow with black legend	450mm	450mm
Northern Ireland	Orange	N/A	Black or orange	Various	450mm	450mm
Other						
Traffic Control	Orange		Orange	Yellow with black legend		
Street Furniture	Black or orange	N/A	Black	Yellow with black legend	450mm	600mm
Communications	Light grey	N/A	Light grey or black	Yellow with black legend		
CCTV	Purple	N/A				
Motorways and Trunk Roads						
England and Wales						
Communications	Purple	N/A	Grey	Yellow with black legend	450mm	
Communications Power	Purple	N/A	Black	Yellow with black legend		
Road Lighting	Orange	N/A	Black	Yellow with black legend		
Scotland						
Communications  	Black or grey	N/A	Black	Yellow with black legend		
Road Lighting	Purple	N/A	Purple	Yellow with black legend		

**These guidelines describe utility industry practice. However, it should not be assumed that all apparatus will conform to the recommendations for positioning and colour coding contained in this publication.**



## **NJUG Guidelines on the Positioning and Colour Coding of Underground Utilities' Apparatus**

*Note: The above tables do not represent an exhaustive list of underground apparatus. Utilities and local authorities do not own all the apparatus that may be found underground. Privately owned pipes and cables exist and their records may not be widely available.*

- All apparatus must be treated with caution until a positive identification has been made. The pipe or duct may have the asset owner's name and contact details stamped upon it. Every effort must be made to avoid damage to all apparatus as the consequences are costly and dangerous.
- The recommended primary method of identification of small buried mains and services and their associated ducts is by colour coding (see Table 1 – 'Recommended Colour Coding of Underground Utilities Apparatus' and Table 2 – 'Recommended Colour Coding of Other Underground Apparatus'. In addition to colour coding, other methods of identification may be used (see sub-section 1.3 – 'Marker / Warning Systems'.
- Reference should also be made to HSE Publication HSG 47, 'Avoiding Danger from Underground Services'

### **1.2 Colour**

#### **1.2.1 New Services**

It is recommended that utilities and other parties use the colour coding shown in Tables 1 and 2 of this document. Where, for example, an electricity company lays gas plant the colour should be that for the service not the owner i.e. all gas pipes should be yellow in colour.

#### **1.2.2 Older Existing Apparatus**

It is important to remember that:

- Older services or other pipelines may not conform to these recommendations.
- Colours may look different under poor or artificial lighting.
- An older pipe or duct could contain apparatus not specifically indicated by its colour coding.
- Aggressive soils may discolour pigments in duct, pipe and cable colourings over time.

## **NJUG Guidelines on the Positioning and Colour Coding of Underground Utilities' Apparatus**

### **1.3 Marker / Warning Systems**

#### **1.3.1 Laying New Marker Systems**

It is recommended that when installing new apparatus appropriate marker systems are laid some distance above the plant. Insulated wire or tapes incorporating a metal strip or passive electronic marker systems may be laid as an aid to the location of non-metallic pipes and ducts. Protection tapes or tiles made out of concrete, clay or plastic may be used and provide an additional means of identification.

#### **1.3.2 Exposing Existing Marker Systems**

When exposing existing marker systems care should be taken that they are not disturbed, damaged or removed. Any displaced marker system should be replaced. Whilst marker systems may have value in warning an operator of the presence of buried plant, they are of strictly limited value as a means of identification. Marker systems should not be taken as an accurate indication of buried plant.


## **2. POSITIONING OF APPARATUS IN A TWO METRE WIDE FOOTWAY**

Figure 1 below illustrates the industry recommended minimum depths of cover to the crown of the apparatus. If in doubt contact the utility apparatus owner for clarification of specific requirements.

## NJUG Guidelines on the Positioning and Colour Coding of Underground Utilities' Apparatus

**FIGURE 1 - Recommended Positioning of Utility Apparatus in a 2 metre Footway**

Note – the same positioning should apply in the carriageway/service strip (if safe and practical to do so) where a development has no footway(s) available for services and/or the boundary of the property is on the carriageway (please refer to minimum depths in carriageways). For further advice please contact the asset owner.



## **NJUG Guidelines on the Positioning and Colour Coding of Underground Utilities' Apparatus**

**The position of pipes and cables shown in Figure 1 is for illustrative purposes only.**

For service connections refer to industry specific by-laws.

*Note: Each utility sector may have its own asset standard in respect to the positioning and depth of apparatus.*

### **3. INSTALLING APPARATUS IN THE CARRIAGEWAY**

In the event of congestion of apparatus in the footway / verge (e.g. where less than 2 metres wide) or where a development has no footway, normal distribution mains, pipes, cables and ducts may have to be sited and positioned within the carriageway. Transmission and trunk main pipes and cable ducts are invariably of larger dimensions and as a consequence may also need to be located in the carriageway.

#### **3.1 Specification for the Reinstatement of Openings in Highways code of practice (SROH)**

Apparatus must be installed below the carriageway construction layers unless special arrangements are made with the relevant authority. Apparatus installed within the carriageway construction is significantly more at risk of damage from traffic loads and excavation and this practice should be avoided whenever possible.

Section 1.8.1 states that undertakers' apparatus greater than 20mm external diameter will not normally be permitted within the road structures.

Section 1.8.2 states that apparatus of 20mm external diameter or less shall not be permitted above or within 20mm of the following levels within a road structure:

- The base (roadbase) / binder course interface in a flexible road.
- The underside of the concrete road slab in a rigid road.
- The underside of modules in a modular road.

In exceptional circumstances, where plant can only be laid within the construction layers of the carriageway, adequate protection should be provided. This should only be considered following consultation and agreement with the relevant authority.

#### **3.2 Ducts**

Where practicable pipes and cables which cross the carriageway should be laid in ducts for ease of future maintenance and the avoidance of congestion.

## NJUG Guidelines on the Positioning and Colour Coding of Underground Utilities' Apparatus

### 3.3 Motorways

Motorways are protected streets and undertakers should avoid laying apparatus under them unless the apparatus is directly associated with the motorway itself (e.g. lighting, communication and signal cables, etc.). Where apparatus does have to be laid under a motorway this is usually accomplished by means of a duct or service tunnel. For procedures regarding protected streets see the code of practice for the Co-ordination of Street Works and Works for Road Purposes and Related Matters.

## 4. INSTALLING APPARATUS OFF THE PUBLIC HIGHWAY

### Industry Recommended Minimum Depths of Cables, Ducts & Mains

The minimum depths to the top of cables / ducts / mains for the various laying conditions are shown in the following tables:

#### 4.1 Electricity

Voltage	Good agricultural land	Footpaths, verges, uncultivated land, pasture agreed to be permanent and land not open to vehicular traffic	
	All situations	Rural	Urban
132kV	910 mm	900 mm	900 mm
66kV	910 mm	750 mm	750 mm
33kV	910 mm	750 mm	750 mm
20kV	910 mm	600 mm	600 mm
11kV	910 mm	450 mm	450 mm
LV & Services	910 mm	450 mm	450 mm

#### 4.2 Water and Waste Water

	Good agricultural land	Footpaths, verges, uncultivated land, pasture agreed to be permanent and land not open to vehicular traffic	
	All situations	Rural	Urban
Minimum Deep ploughing	900 mm As agreed	900 mm As agreed	900 mm As agreed

## NJUG Guidelines on the Positioning and Colour Coding of Underground Utilities' Apparatus

### 4.3 Communications

	Good agricultural land	Footpaths, verges, uncultivated land, pasture agreed to be permanent and land not open to vehicular traffic	
	All situations	Rural	Urban
Minimum	350 mm	350 mm	350 mm
Deep ploughing	As agreed	As agreed	As agreed

### 4.4 Gas

		Service Diameters ≤63 mm / 2"	All Other Pipes			
			2 bar or below	> 2 bar to 7 bar	> 7 bar to 16 bar	> 16 bar
Open fields and agricultural land	Min.	1100 mm	1100 mm	1100 mm	1100 mm	1100 mm
	Deep ploughing	By agreement	By agreement	By agreement	By agreement	By agreement
Rural & urban locations	Paved footways	450 mm	600 mm	600 mm	1100 mm	1100 mm
	Verges & private roads	By agreement	750 mm	750 mm	1100 mm	1100 mm
	Uncultivated land, pasture agreed to be permanent and land not open to vehicular traffic	1100 mm	1100 mm	1100 mm	1100 mm	1100 mm

**Contact must be made with the Gas Network Operator before any installation or excavation work is undertaken**

## 5. FACTORS INFLUENCING THE POSITIONING OF UNDERGROUND APPARATUS

Due to technical, engineering or legal constraints there may be occasions where these recommendations cannot be adhered to. Examples include:

- (a) Width restrictions
- (b) Depth restrictions
- (c) Environmental reasons e.g. trees and planted areas

## **NJUG Guidelines on the Positioning and Colour Coding of Underground Utilities' Apparatus**

- (d) Restrictions imposed by legislation
- (e) Safe access to apparatus e.g. heavily trafficked roads
- (f) Clustering of utilities' apparatus typically caused by:
  - Jointing chambers or valve installations in footways which may reduce the available space for additional apparatus.
  - Apparatus exiting from or entering buildings or chambers e.g. electricity substations and telephone exchanges.
  - Surface apparatus e.g. kiosks, street lighting columns and cabinets.

In such circumstances apparatus may be forced to encroach into adjacent private property providing the necessary permissions have been obtained.

### **6. TRENCH SHARING**

Trench sharing may be beneficial in reducing disruption to both vehicular and pedestrian traffic, as well as offering cost savings in construction methods and reinstatement liability for utilities. Trench sharing can also be useful in maximising the limited available space in the highway.

Wherever practical and appropriate trench sharing should be considered.

When trench sharing is an option it is essential that early consultation takes place with representatives from relevant authorities and all other interested parties.

Agreement on the positioning of apparatus within a shared trench together with the reinstatement specification should be made between all interested parties (including the relevant authority) as early as possible as part of the planning process.

A primary promoter should be identified to take overall responsibility as the agreed point of contact with the relevant authority. The primary promoter would normally excavate the trench and install its own apparatus. The secondary promoter/s would then install their apparatus in the same trench. The primary promoter would then backfill the trench and reinstate unless an alternative agreement has been made.

With regard to statutory noticing and permit requirements it is the responsibility of each party to individually notify their own works.

*For further guidance see the Code of Practice for the Co-ordination of Street Works and Works for Road Purposes and Related Matters.*

## **NJUG Guidelines on the Positioning and Colour Coding of Underground Utilities' Apparatus**

### **7. COMBINED SERVICE DUCTS, SUBWAYS AND TUNNELS**

There are circumstances where utilities may be required to install their apparatus in designated service ducts, subways and tunnels. When considering these options the following should be taken into account:

- Accessibility - when considering the positioning of apparatus, access and maintenance.
- Positioning of apparatus – as directed by the asset owner.

### **8. USE OF ABANDONED AND SURPLUS APPARATUS**

Abandoned or surplus apparatus is occasionally used by other utilities. While this avoids unnecessary excavation and potential damage to third party apparatus it is essential that both the original and new owners record the change of utility use and plant records are updated accordingly.

Any new apparatus installed should be colour coded in accordance with Table 1 – 'Recommended Colour Coding of Underground Utilities Apparatus'.

Arrangements for the use of such apparatus between asset owners will be unique to each utility and can only be made by mutual agreement.

### **9. DISTRICT HEATING**

A district heating installation typically consists of a highly insulated "heat main" of flow and return pipes distributing hot water (or steam) to buildings which are connected via junction points.

The proximity of district heating apparatus may affect the efficiency and operation of other underground apparatus. Before such apparatus is laid contact must be made with all appropriate existing apparatus owners.

Installers of district heating should consider the location, spacing and depth of cover to avoid potential conflict with other existing underground apparatus.

Owners of other underground apparatus should be aware of the potential safety issues and dangers of working in proximity to district heating apparatus and should make contact with the existing owners of such apparatus. The local authority may be able to advise as to the ownership of the district heating network.



## NJUG Guidelines on the Positioning and Colour Coding of Underground Utilities' Apparatus

### GLOSSARY

<b>Apparatus</b>	Equipment such as valves, stopcocks, chambers, cabinets, transformer chambers etc and includes any structure for the lodging of apparatus.
<b>Carriageway</b>	A way constituting or comprised in a highway, being a way (other than a cycle track) over which the public have a right of way for the passage of vehicles.
<b>Cycle track</b>	A way constituting or comprised in a highway over which the public have a right of way on pedal cycles with or without a right of way on foot.
<b>District heating</b>	District heating utilizes a centralized boiler installation to provide heat for a number of buildings such as individual houses, blocks of social housing, local council offices, schools etc.
<b>Duct / ducting</b>	Structure (usually cylindrical) used to convey and protect apparatus
<b>Fibre optic</b>	The use of very thin glass or plastic fibres through which light can be transmitted to carry information from a source to a receiver, especially for telecommunication, television and information technology systems.
<b>Footpath</b>	A highway over which the public have a right of way on foot only, not being a footway.
<b>Footway</b>	A way comprised in a highway which also comprises a carriageway, being a way over which the public have a right of way on foot only.
<b>GRP</b>	Glass Reinforced Plastic
<b>High Voltage</b>	Electricity cables over 1000 volts (>1kV)
<b>Low Voltage</b>	Electricity cables up to and including 1000 volts (1kV)
<b>Main</b>	Structure (usually cylindrical) used to convey water or gas or oil generally greater than 50mm diameter.
<b>NJUG</b>	National Joint Utilities Group Limited.
<b>Pipe</b>	Longitudinal structure (usually cylindrical) used to convey water, gas or oil.
<b>Service strip</b>	A strip of designated land alongside a carriageway or footway used to convey services.
<b>Sub-duct</b>	Longitudinal structure (usually cylindrical) laid inside ducts used to carry smaller diameter cables such as fibre optic.



The National Joint Utilities Group

## **NJUG Guidelines on the Positioning and Colour Coding of Underground Utilities' Apparatus**

<b>Tiles</b>	Impact resistant cover constructed of earthenware, concrete or polyethylene for protecting underground cables
<b>Utility</b>	An undertaker by statute that has a legal right to provide customer services (e.g. communications, electricity, gas, water)
<b>Verge</b>	A strip of land which may form part of the public highway alongside a carriageway or footway, which may contain services.

## **APPENDIX A**

### **Important Legal Notice and Disclaimer**

1. This publication describes utility industry practice and gives guidelines on the positioning and colour coding of underground utilities' apparatus. NJUG has endeavoured to ensure that the information is correct and up-to-date at the date of first publication, but does not warrant its completeness and accuracy or that it will remain up-to-date. This publication is not intended to be exhaustive and may not be applicable in all situations.
2. You are permitted to print and download and make photocopies of this publication for your own use only on the following basis:
  - a) none of the information or related graphics in this publication are modified in any way;
  - b) no graphics in this publication are used separately from accompanying text; and
  - c) NJUG's copyright notices and this Legal Notice and Disclaimer are to appear in all copies
3. Unless otherwise stated, the copyright and other intellectual property rights in this publication are owned by NJUG Ltd or its licensors. For the purposes of this legal notice, any use of extracts from this publication other than expressly permitted by this legal notice, is prohibited. If you breach any of the terms in this legal notice, your permission to use this publication automatically terminates.
4. No part of this publication may be reproduced in any way (including via any website) or stored in any public or private electronic retrieval system or service without NJUG's prior written permission. Any rights not expressly granted in this legal notice are reserved.
5. This publication has no legal or statutory authority and is not intended to be a definitive or complete statement of the applicable law. Reference should always be made to any relevant legislation. This publication is not intended to be or to replace specific legal advice and all persons acting or placing reliance on this publication or any part of it are advised to consult with their own legal advisors to ensure that they understand and comply with the legal requirements which are applicable to their organisation and circumstances.

## **NJUG Guidelines on the Positioning and Colour Coding of Underground Utilities' Apparatus**

6. Persons who act or place reliance on this publication are solely responsible for undertaking all surveys, enquiries, tests and other investigations as may be appropriate in the circumstances. NJUG Ltd and its directors, advisors and other contributors to this publication (together collectively referred to as 'NJUG') do not accept any responsibility for the actions or conclusions drawn by persons acting or placing reliance on this publication.
7. This publication is free of charge and persons relying on this publication acknowledge that it would be unreasonable to hold NJUG liable in respect of this publication and the information contained in it. NJUG excludes all liability to the maximum extent permitted under applicable law. NJUG shall not be liable for any direct, indirect or consequential losses, damage, costs or expenses whatsoever or howsoever sustained by any person acting or placing reliance on this publication (or any person or entity claiming through such person) or otherwise arising therefrom – whether arising in tort, contract or otherwise – including, without limitation, any loss of profits, contracts, business, goodwill, data, income, revenue or anticipated savings.
8. Nothing in this disclaimer shall exclude or limit NJUG's liability for death or personal injury arising from its negligence, nor any other matter which cannot be excluded or limited under applicable law.

**These guidelines describe utility industry practice. However, it should not be assumed that all apparatus will conform to the recommendations for positioning and colour coding contained in this publication.**