

## Safety lamps

Reference	Characteristics	mm	kg
<b>CD-122</b>	Automatic switch on in case of power break Adjustable flood beam - power beam: 5.5 W Operates: 3 hours - IP40 Classe II	240 x 120 x 128	1.8
<b>CD-124</b>	Delivered with a wall mounted support. Operates: 1 hour (12 W), 2 hours (6 W) Rechargeable on 230 V 50/60 Hz	100 x 190 x 220	1.9



CD-124



CD-122

## Aperture Housing

Compatible with **NF C 13-100**.

Moulded plastic. Installed outside by tightening three screws on a steel clamp.

Reference	g
<b>CI-70</b>	140



Passage Ø 60 mm.

## Manœuvring and rescue sticks

White resin polyester/glass fiber foam filled tube.

Reference			g
<b>CM-45</b>	45 kV	1.50 m	7 500
<b>CS-45 *</b>	45 kV	1.65 m	1 000
<b>CM-90</b>	90 kV	1.85 m	800
<b>CS-90 *</b>	90 kV	2.05 m	1 100
<b>CM-225</b>	225 kV	2.25 m	850
<b>CS-225 *</b>	225 kV	2.45 m	1 350

\* Delivered with wall mounted supports.



Manœuvring stick.

Rescue stick.

CM-45

CS-45



Extra safety equipment and life saving kits

## Wall mounted supports

For sticks and voltage detectors. Plastic.

Reference	Top ∅ mm	Bottom ∅ mm
CI-06-D	28-30	36 max.
CI-08	16-20	36 max.
CI-10-D	32-36	58 max.
CI-12-D	28-30	58 max.

Delivered with wood screws.



## Rescue hook

Reference	Characteristics	mm	g
CS-01-C	Adaptor C	345 x 335	350

On stick equipped with a "C" end-fitting.



## Compact carrying KIT

This compact kit is designed especially to be carried in a vehicle for safety electrical intervention.

Made of two parts (of moulded material: PEHD), the red case cover is also an insulating platform.

Reference	Characteristics with instructions in English	~	mm	kg
CZ-53-R	With instructions in English	25 kV	710 x 570 x 240	21
CZ-53-MR	With instructions in English/Arabic	25 kV	710 x 570 x 240	21
CZ-53-R/2	With instructions in English	36 kV	710 x 570 x 240	21
CZ-53-MR/2	With instructions in English/Arabic	36 kV	710 x 570 x 240	21

