



## LIFE SAVING KITS FOR M.V. SUBSTATIONS

Complete equipment allowing intervention on victims in case of an electrical hazard. Delivered in a plastic box with transparent cover for immediate visualization of contents and wall mounting kit.

### Composition :

- Insulated cable cutter. Forged steel blades. Maximum opening 30 mm. (CZ-60)
- Insulating platform 24 or 36 kV. (CT-7-25/1)
- Rescue telescopic stick. (M952160)
- Voltage detector with flexible antenna contact (with autotest). (M952170)
- Safety instructions on the plastic board. (CG-3-10-NR/CZ-54)
- High voltage insulating gloves, talcum powder can. (CG-4-10-NR/CZ-55) - (CG-3-10-NR/CZ-54)
- Insulating boots. (MV-137-45)
- Wall mounted cabinet.



Reference	Characteristics	~	mm	kg
<b>CZ-54-R</b>	English instructions	24 kV	840 x 754 x 270	21
<b>CZ-54-RM</b>	English/Arabic instructions	24 kV	840 x 754 x 270	21
<b>CZ-55-R</b>	English instructions	36 kV	840 x 754 x 270	21
<b>CZ-55-RM</b>	English/Arabic instructions	36 kV	840 x 754 x 270	21

## THE ⊕

- 1 Emergency supplies at your fingertips.
- 2 Protection against dust and shock.

## INFO

In case of an electrical accident, quick action is essential: by saving seconds, you get more chance to save life. Our life saving equipment is designed to make all necessary equipment immediately available to rescue people.

## INSULATED CABLE CUTTER

Insulated handles 25 kV.  
Maxi cable : 30 mm.  
Section ≈ 150 mm<sup>2</sup>.  
Maximum opening: 30 mm.

Reference	↔	kg
<b>CZ-60</b>	0.630 m	2.2



## WALL MOUNTED SUPPORTS

For sticks and voltage detectors. Plastic.

Reference	∅ mm	Top	∅ mm	Bottom
CI-06-D		28-30		36 max.
CI-08		16-20		36 max.
CI-10-D		32-36		58 max.
CI-12-D		28-30		58 max.



## RESCUE HOOK

On stick equipped with a "C" end-fitting. Delivered with wall mounted supports.

Reference	Characteristics	mm	kg
CS-01-C	Adaptor C	345 x 335	0.35



## COMPACT CARRYING KIT

This compact kit is designed especially to be carried in a vehicle for safety electrical intervention. Made of two parts of moulded material (PEHD), the red case cover is also an insulating platform.

### Composition :

- Insulated cutter cable.
- Adhesive tape (black and yellow). L = 100 m.
- Telescopic insulating stick. L = 1.5 m.
- Talcum powder can.
- Pair of insulating boots.
- Voltage detector with autotest. Rescue hook. (127 V - 90 kV alternatif)
- Pair of insulating gloves with reinforced carrying bag.
- Safety instructions and safety first aid posters.
- Insulating platform.

Reference	Characteristics with instructions in English	~	mm	kg
CZ-53-R	With instructions in English	25 kV	710 x 570 x 240	21
CZ-53-MR	With instructions in English/Arabic	25 kV	710 x 570 x 240	21
CZ-53-R/2	With instructions in English	36 kV	710 x 570 x 240	21
CZ-53-MR/2	With instructions in English/Arabic	36 kV	710 x 570 x 240	21

THE 

1 Stability of the suitcase when stored vertically or horizontally.



∅ Diameter   ← Total length   mm Dimensions    Weight



THORNE & DERRICK INTERNATIONAL

Thorne & Derrick  
+44 (0) 191 410 4292  
www.powerandcables.com

MV Substation equipment / Life saving kits

**GATU™**

#167