



LIFE SAVING KITS FOR M.V. SUBSTATIONS

Complete equipment allowing intervention on victims in case of an electrical hazard. Delivered in a plastic box with transparent cover for immediate visualization of contents and wall mounting kit.

Composition :

- Insulated cable cutter. Forged steel blades. Maximum opening 30 mm. (CZ-60)
- Insulating platform 24 or 36 kV. (CT-7-25/1)
- Rescue telescopic stick. (M952160)
- Voltage detector with flexible antenna contact (with autotest). (M952170)
- Safety instructions on the plastic board. (CG-3-10-NR/CZ-54)
- High voltage insulating gloves, talcum powder can. (CG-4-10-NR/CZ-55) - (CG-3-10-NR/CZ-54)
- Insulating boots. (MV-137-45)
- Wall mounted cabinet.



Reference	Characteristics	~	mm	kg
CZ-54-R	English instructions	24 kV	840 x 754 x 270	21
CZ-54-RM	English/Arabic instructions	24 kV	840 x 754 x 270	21
CZ-55-R	English instructions	36 kV	840 x 754 x 270	21
CZ-55-RM	English/Arabic instructions	36 kV	840 x 754 x 270	21

THE ⊕

- 1 Emergency supplies at your fingertips.
- 2 Protection against dust and shock.

INFO

In case of an electrical accident, quick action is essential: by saving seconds, you get more chance to save life. Our life saving equipment is designed to make all necessary equipment immediately available to rescue people.

INSULATED CABLE CUTTER

Insulated handles 25 kV.

Maxi cable : 30 mm.

Section ≈ 150 mm².

Maximum opening: 30 mm.

Reference	↔	kg
CZ-60	0.630 m	2.2



WALL MOUNTED SUPPORTS

For sticks and voltage detectors. Plastic.

Reference	∅ mm	Top	∅ mm	Bottom
CI-06-D		28-30		36 max.
CI-08		16-20		36 max.
CI-10-D		32-36		58 max.
CI-12-D		28-30		58 max.



RESCUE HOOK

On stick equipped with a "C" end-fitting. Delivered with wall mounted supports.

Reference	Characteristics	mm	kg
CS-01-C	Adaptor C	345 x 335	0.35



COMPACT CARRYING KIT

This compact kit is designed especially to be carried in a vehicle for safety electrical intervention. Made of two parts of moulded material (PEHD), the red case cover is also an insulating platform.


Composition :

- Insulated cutter cable.
- Adhesive tape (black and yellow). L = 100 m.
- Telescopic insulating stick. L = 1.5 m.
- Talcum powder can.
- Pair of insulating boots.
- Voltage detector with autotest. Rescue hook. (127 V - 90 kV alternatif)
- Pair of insulating gloves with reinforced carrying bag.
- Safety instructions and safety first aid posters.
- Insulating platform.

Reference	Characteristics with instructions in English	~	mm	kg
CZ-53-R	With instructions in English	25 kV	710 x 570 x 240	21
CZ-53-MR	With instructions in English/Arabic	25 kV	710 x 570 x 240	21
CZ-53-R/2	With instructions in English	36 kV	710 x 570 x 240	21
CZ-53-MR/2	With instructions in English/Arabic	36 kV	710 x 570 x 240	21

THE

1 Stability of the suitcase when stored vertically or horizontally.



∅ Diameter ← Total length mm Dimensions Weight



THORNE & DERRICK INTERNATIONAL

Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com

MV Substation equipment / Life saving kits



#167