

COPPER TUBE LUGS 4-ESI FIXING A-4ESI



THORNE &
DERRICK
INTERNATIONAL

Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com

A-4ESI series lugs are made from high purity electrolytic copper tube, annealed and tin plated. The four hole stud fixing in accordance with E.A. specifications ensures compatibility with most transformer fixing arrangements.



Technical characteristics


Material (Body)

Tinned electrolytic copper electrolytically

Material (Fixing)

Tinned electrolytic copper electrolytically

Media gallery



List of products

➤ A-4ESI Cable type: copper, Maximum section: 185 mm²



Type	B	L	Number the hole	Pack qty	Min. pack qty	M	N	Center distances	Øi
A37-4ESI	61 mm	124 mm	4	20	10	20 mm	15 mm	25L-35B	19.2 mm

➤ A-4ESI Cable type: flexible copper, Maximum section: 185 mm²





Type	B	L	Number the hole	Pack qty	Min. pack qty	M	N	Center distances	Øi
A37-4ESI	61 mm	124 mm	4	20	10	20 mm	15 mm	25L-35B	19.2 mm

A-4ESI Cable type: copper, Maximum section: 240 mm²



Type	B	L	Number the hole	Pack qty	Min. pack qty	M	N	Center distances	Øi
A48-4ESI	61 mm	128 mm	4	20	10	20 mm	15 mm	25L-35B	21.1 mm

A-4ESI Cable type: flexible copper, Maximum section: 240 mm²



Type	B	L	Number the hole	Pack qty	Min. pack qty	M	N	Center distances	Øi
A48-4ESI	61 mm	128 mm	4	20	10	20 mm	15 mm	25L-35B	21.1 mm

A-4ESI Cable type: flexible copper, Maximum section: 300 mm²



Type	B	L	Number the hole	Pack qty	Min. pack qty	M	N	Center distances	Øi
A60-4ESI	61 mm	133 mm	4	15	5	20 mm	15 mm	25L-35B	23.7 mm

A-4ESI Cable type: copper, Maximum section: 300 mm²



Type	B	L	Number the hole	Pack qty	Min. pack qty	M	N	Center distances	Øi
A60-4ESI	61 mm	133 mm	4	15	5	20 mm	15 mm	25L-35B	23.7 mm

A-4ESI Cable type: flexible copper, Maximum section: 400 mm²



Type	B	L	Number the hole	Pack qty	Min. pack qty	M	N	Center distances	Øi
A80-4ESI	61 mm	134 mm	4	15	5	20 mm	15 mm	25L-35B	27 mm

A-4ESI Cable type: copper, Maximum section: 400 mm²



Type	B	L	Number the hole	Pack qty	Min. pack qty	M	N	Center distances	Øi
A80-4ESI	61 mm	134 mm	4	15	5	20 mm	15 mm	25L-35B	27 mm

> A-4ESI Cable type: flexible copper, Maximum section: 500 mm²



Type	B	L	Number the hole	Pack qty	Min. pack qty	M	N	Center distances	Øi
A100-4ESI	61 mm	139 mm	4	10	5	20 mm	15 mm	25L-35B	30.3 mm

> A-4ESI Cable type: copper, Maximum section: 500 mm²



Type	B	L	Number the hole	Pack qty	Min. pack qty	M	N	Center distances	Øi
A100-4ESI	61 mm	139 mm	4	10	5	20 mm	15 mm	25L-35B	30.3 mm

> A-4ESI Cable type: flexible copper, Maximum section: 630 mm²



Type	B	L	Number the hole	Pack qty	Min. pack qty	M	N	Center distances	Øi
A120-4ESI	61 mm	144 mm	4	10	5	20 mm	15 mm	25L-35B	33.4 mm

> A-4ESI Cable type: copper, Maximum section: 630 mm²



Type	B	L	Number the hole	Pack qty	Min. pack qty	M	N	Center distances	Øi
A120-4ESI	61 mm	144 mm	4	10	5	20 mm	15 mm	25L-35B	33.4 mm

> A-4ESI Cable type: flexible copper, Maximum section: 800 mm²



Type	B	L	Number the hole	Pack qty	Min. pack qty	M	N	Center distances	Øi
A160-4ESI	61 mm	158 mm	4	8	1	20 mm	15 mm	25L-35B	38 mm

A-4ESI Cable type: copper, Maximum section: 800 mm²



Type	B	L	Number the hole	Pack qty	Min. pack qty	M	N	Center distances	Øi
A160-4ESI	61 mm	158 mm	4	8	1	20 mm	15 mm	25L-35B	38 mm



THORNE &
DERRICK
INTERNATIONAL

Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com