



**Section**

MV Insulation

**Application**

Field



**PRODUCT BENEFITS**

Ruler to set the length of insulation to be removed  
 Back-iron to set the pitch of the tool making easy to rotate the tool

**TOOL CAPACITY**

**Diameter** 38 - 60 mm  
 1,496 - 2,362 inch

**Max cutting depth** 17 mm / 0,669 in

**TOOL DIMENSIONS**

**Length** 425 mm

**Width** 105 mm

**Height** 85 mm

**Weight without box** 2 Kg

**Packaging** None

## Monofunction tool for insulation

**TO DO WHAT**

The LH2 enables the user to remove the insulation



**Spare part**

LAC2 - Spare blade for insulation

**Associated tool**

LHS2 - Monofunction tool for semiconductor

PRG3-C20L222830 - Pliers for MV cable outer sheath with 3 adjustable longitudinal cutting depth

BMF2 - Thrust to stop the tool



**THORNE &  
 DERRICK  
 INTERNATIONAL**

**Thorne & Derrick**

+44 (0) 191 410 4292

www.powerandcables.com



Part Number	D iameter	Tool capacity	D imensions			Packaging
		Max cutting depth	Length	Width	Height	
LH2	38 - 60 mm 1,496 - 2,362 in	17 mm / 0,669 in	425 mm 16,732 in	105 mm 4,134 in	85 mm 3,346 in	none
LH3	60 - 80 mm 2,362 - 3,150 in	24 mm / 0,945 in	460 mm 18,110 in	130 mm 5,118 in	85 mm 3,346 in	none
LH4	80 - 110 mm 3,150 - 4,331 in	29 mm / 1,142 in	640 mm 25,197 in	155 mm 6,102 in	95 mm 3,740 in	none
LH5	100 - 140 mm 3,937 - 5,512 in	35 mm / 1,378 in	730 mm 28,740 in	195 mm 7,677 in	115 mm 4,528 in	case

