



Section

MV Outer sheath

Application

Field
Laboratory
Production



PRODUCT BENEFITS

Quick, light and easy to use

TOOL CAPACITY

Diameter 26 - 52 mm
1,024 - 2,047 inch

Circular cutting thickness capacity 2,5 mm / 0,098 in

Longitudinal cutting thickness capacity 3,0 mm / 0,118 in

TOOL DIMENSIONS

Length 265 mm

Width 95 mm

Height 80 mm

Weight without box 0,6 Kg

Packaging None

Pliers for MV cable outer sheath

TO DO WHAT

The PG3HTA/2530 enables the user to make a circular and longitudinal cut in order to remove cable's outer sheath

All cutting depth ranging from 0,5 mm / 0,019 in to 5 mm / 0,196 in are available on demand

How to built your customized pliers : PG3HTA/yyzz

yy = Circular cutting depth e.g : 25 = 2,5 mm / 0,098 in

zz = Longitudinal cutting depth e.g : 30 = 3,0 mm / 0,118 in



Options

SGM - Large size pouch

Spare part

MTC3/25 - Spare blade for circular cutting 2,5 mm / 0,098 in (x4)

MTL3/30 - Spare blade for longitudinal cutting 3,0 mm / 0,118 in

Associated tool

MF1+/25 - Multifunction tool for bonded semiconductor

MF2/40 - Multifunction tool for outer sheath and insulation



**THORNE &
DERRICK
INTERNATIONAL**

Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com



Part Number	D iameter	Tool capacity		D imensions			Packaging
		Circular cutting thickness capacity	Longitudinal cutting thickness capacity	Length	Width	Height	
PG2HTA/2828	21 - 35 mm 0,827 - 1,378 in	2,8 mm / 0,110 in	2,8 mm / 0,110 in	240 mm 9,449 in	85 mm 3,346 in	80 mm 3,150 in	none
PG3HTA/2530	26 - 52 mm 1,024 - 2,047 in	2,5 mm / 0,098 in	3,0 mm / 0,118 in	265 mm 10,433 in	95 mm 3,740 in	80 mm 3,150 in	none
PG3HTA/2828	26 - 52 mm 1,024 - 2,047 in	2,8 mm / 0,110 in	2,8 mm / 0,110 in	240 mm 9,449 in	85 mm 3,346 in	80 mm 3,150 in	none
PG3HTA/2833	26 - 52 mm 1,024 - 2,047 in	2,8 mm / 0,110 in	3,3 mm / 0,130 in	265 mm 10,433 in	95 mm 3,740 in	80 mm 3,150 in	none
PG4HTA/3033	47 - 75 mm 1,850 - 2,953 in	3,0 mm / 0,118 in	3,3 mm / 0,130 in	300 mm 11,811 in	110 mm 4,331 in	105 mm 4,134 in	none
PG5HTB /3535	69 - 95 mm 2,717 - 3,740 in	3,5 mm / 0,138 in	3,5 mm / 0,138 in	360 mm 14,173 in	140 mm 5,512 in	160 mm 6,299 in	none
PG6HTB /3535	90 - 125 mm 3,543 - 4,921 in	3,5 mm / 0,138 in	3,5 mm / 0,138 in	515 mm 20,276 in	195 mm 7,677 in	200 mm 7,874 in	none
PG6HTB /4040	90 - 125 mm 3,543 - 4,921 in	4,0 mm / 0,157 in	4,0 mm / 0,157 in	515 mm 20,276 in	195 mm 7,677 in	200 mm 7,874 in	none
PG7HTB /3535	120 - 170 mm 4,724 - 6,693 in	3,5 mm / 0,138 in	3,5 mm / 0,138 in	515 mm 20,276 in	195 mm 7,677 in	200 mm 7,874 in	none

