



THORNE &
DERRICK
INTERNATIONAL

Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com

Item Code: **SM550**

Item Description: **Fine Ribbed Rubber Matting [Previously BS921/1976]**

SM550 Fine Ribbed Rubber Matting Previously BS921/1976 is a high quality, British industry electrical safety matting to British Standard BS921/1976 with the regulation standard stamped on the reverse of the roll at 1000mm intervals. Fully certified and tested to 15,000 volts with a recommended safety working voltage of 650v. It has a fine ribbed, anti-slip surface pattern on one side and cloth impression finish on reverse.

- Fully tested to British Standard
- Health & Safety regulation material
- Fully traceable supply
- Regulatory branding on reverse
- Anti-Slip finish
- Low maintenance

Cut lengths available to order. SM550 can also be supplied to order in colours and flame retardant, low smoke emission grades

Technical Information

Application	Electrical Safety, General Purpose, Health & Safety
Product	Anti Slip, Electrical Safety, Safety Matting
Thickness	9.5mm
Resistance to	Please Call
Colour	Black
Insert Req	No
Solid	Yes
Drainage Holes	No

metroseal a division of Accrasystem Limited

Units 28 & 30, Purdeys Way, Purdeys Industrial Estate, Rochford, Essex SS4 1ND UK

tel: 01702 548800 fax: 01702 549966 email: sales@metroseal.co.uk



**THORNE &
DERRICK
INTERNATIONAL**

Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com

Item Code: SM550

Other sizes and colours to special order.
Cut lengths to order.

All recommendations and information contained in this specification sheet are to the best of our knowledge correct. Since conditions of service are beyond our control, users must satisfy themselves that the products are suitable for the intended use. No warranty is given or implied in respect of information or recommendations or that any use of products will infringe rights belonging to other parties. In any event or occurrence our liability is limited to the invoice value of our goods delivered to you. We reserve the right to change product design and properties without notice.



Stock Roll Sizes	Weight	Specifications	Values
[m x m x mm]	[kg/M2]	[compound]	[typical]
10m x 0.91m x 9.5mm	12.00	Colour:	Black
10m x 1.0m x 9.5mm	12.00	Compound:	SBR/NR
10m x 1.2m x 9.5mm	12.00	Hardness [shore A]:	65°
		Density[SG]:	1.3
		Tensile Strength:	5 MPA
		Elongation[min]:	250%
		Abrasion Resistance:	180 mm ³
		Minimum Temperture	-20°C
		Maximum Temperture	+70°C

metroseal a division of Accrasystem Limited

Units 28 & 30, Purdeys Way, Purdeys Industrial Estate, Rochford, Essex SS4 1ND UK

tel: 01702 548800 fax: 01702 549966 email: sales@metroseal.co.uk