PO7000 HYDRULIC PUMP WITH INSULATED FOOT PEDAL

Description:

The hydraulic pump develops a maximum pressure of 700 bar (10,000 psi) and is suitable for connection to a Cembre hydraulic KV version head.
Contains non-conductive oil with a high insulating power and the foot pedal is protected with orange plastic material.
Pressure can be withdrawn at any time during operation by depressing the release lever.
A solid shaped stand gives the pump stability during operation.

General Characteristics:

– Max operating pressure:	700 bar	(10,000 psi)
– Dimensions:		
length	680 mm	(26.7 in.)
width	200 mm	(7.9 in.)
height	163 mm	(6.4 in.)
– Weight (pump without hose):	9,2 kg	(20.3 lbs)
– Oil reservoir capacity:	1000 cm^3	(33.8 USA fl.oz.)
– Non-conductive oil:	AGIP ITE 360	or
	ESSO TRANSFORMER OIL P 60	or
	MOBIL MOBILECT 46	or equivalent

– Two speed operation: the first stage is low pressure for rapid approach, with automatic switching to the second high pressure stage, for crimping or cutting.

– Safety: the pump is provided with max pressure valve; a special hydraulic gauge (MPC 1) is available, on request, to check the correct setting of the valve.

Cembre SpA
Via Serenissima, 9 - 25135 Brescia (Italy)
Tel.: +39 030 36921 - Fax: +39 030 3365766
Web: www.cembre.com - Email: info@cembre.com

Prepared by: Marketing dept. *Date: 03/09/2009*