


A TYPE - HIGH STRENGTH CABLE GRIP



This is the strongest grip we produce. It can be used for conductor and synthetic rope pulls. A Type grips are colour coded for ease of identification. Perfect for overhead transmission and distribution line pulling projects or any other pulling applications with heavy load ratings such as electric railroad, rigging lines and construction pulls. When pulling synthetic rope use a Slingco Feed Tube (see page 22) to make inserting rope into the grip a breeze. Made of galvanised steel. To avoid the effects of torsion a line pulling swivel that rotates under load should be used with pulling grips.




Slingco Part No	Color Code	Rope Diameter Range		Conductor Diameter Range		Overall length		Lattice Length		Approx. Break Load	
		in	mm	in	mm	in	mm	in	mm	lb	kg
ZCS1799	Black	0.25 - 0.65	6-16	0.19 - 0.40	5-10	38	965	28	710	7,000	3,180
ZCS3020	Purple	0.30 - 0.40	7.5-10	0.25 - 0.40	6-10	42	1,067	30	760	10,000	4,530
ZCS1800	Dark Green	0.50 - 0.90	13-23	0.38 - 0.63	9.7-16	43	1,092	37	940	14,000	6,360
ZCS3522	Grey	0.44 - 0.90	11-23	0.44 - 0.63	11-16	110	2,800	97	2,470	20,000	9,072
ZCS1801	Red	0.75 - 1.10	19-28	0.63 - 0.88	16-22	74	1,880	58	1,473	20,000	9,072
ZCS1802	Blue	1.00 - 1.50	25-38	0.88 - 1.12	22-29	80	2,032	61	1,549	30,700	13,955
ZCS1803	Yellow	1.25 - 1.70	32-43	1.13 - 1.38	29-35	112	2,845	90	2,299	47,000	21,360
ZCS1804	Aluminum	1.50 - 2.10	38-53	1.38 - 1.90	35-50	119	3,020	92	2,336	67,000	30,455

R TYPE - ROTATING MULTI-WEAVE GRIP

Like the MU type, the rotating eye grip has a triple weave construction and is colour coded for ease of identification. The steel forged revolving head is ideal for connecting to Slingco swivels. Warning: The Slingco rotating eye does not revolve under load and does not replace the use of a line swivel. Please see page 17 for swivel and grip match-up and safety and technical information. Made of galvanised steel.



Slingco Part No	Colour Code	Range		Lattice Length		Approx. Break Load	
		in	mm	in	mm	lb	kg
ZCS2177	Dark Green	0.25 - 0.50	6-12	31	787	7,000	3,170
ZCS2178	Brown	0.50 - 0.75	12-19	45	1,143	10,500	4,760
ZCS2179	Light Blue	0.75 - 1.00	19-25	43	1,092	14,100	6,395
ZCS2180	Gold	1.00 - 1.25	25-32	65	1,651	25,000	11,340
ZCS2181	Black	1.25 - 1.50	32-38	59	1,499	31,000	14,065
ZCS2182	Red	1.50 - 1.75	38-44	82	2,083	31,000	14,065
ZCS2183	Dark blue	1.75 - 2.25	44-57	82	2,083	43,000	19,510
ZCS2779	Yellow	2.00 - 2.50	50-63	72	1,829	43,000	19,510
ZCS2780	Orange	2.50 - 3.00	63-76	72	1,829	43,000	19,510
ZCS2781	Aluminium	3.00 - 3.50	76-89	74	1,880	43,000	19,510
ZCS2782	Light Green	3.50 - 4.00	89-102	76	1,930	43,000	19,510



**THORNE &
DERRICK
INTERNATIONAL**

Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com