SPECIFICATION SHEET



PRODUCT: Detectamesh®

DESCRIPTION:

Polypropylene mesh laminated with a 50mm wide printed polyethylene warning band top tape and incorporating a stainless steel tracer wire. Wire conforms to BS1554. Mesh manufactured to EN12613.

PHYSICAL CHARACTERISTICS:	
BASE COLOUR	See page 2
PRINT COLOUR	Black
TEXT	See page 2

DIMENSIONAL CHARACTERISTICS:	
ROLL WIDTH	200mm
ROLL LENGTH	100m
ROLL DIAMETER	250mm
MESH WEIGHT	70g/mm2
APERTURE SIZE	95 x 20mm
WIRE DIAMETER	0.4mm

MESH TECHNICAL CHARACTERISTICS:	
Measurements	Results
TENSILE STRENGTH	>3.5N/mm2
ELONGATION @ YIELD	>15%
ELONGATION @ BREAK	>35%

For and on behalf of Boddingtons Limited

Whi Good.

Quality Manager

All the above information is given in good faith, but the figures are typical values only and should not be taken as a guarantee of performance. Manufacturing tolerances for dimensional and technical characteristics apply and are available on request. The company reserves the right to improve the product and adjust the specification without notice.

SPEC: 016747 Issue: 2 Page 1of 2 Date: May 2008





PRODUCT: Detectamesh®

STANDARD TEXTS AVAILABLE FI	ROM STOCK
CAUTION-WATER MAIN BELOW	CAUTION-SEWERAGE PUMPING MAIN BELOW
CAUTION - STORM WATER CULVERT BELOW	CAUTION-GRAVITY SEWER BELOW
CAUTION-BURIED GAS PIPE	CAUTION-PRESSURE SEWER BELOW
CAUTION•ELECTRIC CABLE BELOW	CAUTION-NON POTABLE WATER MAIN BELOW
CAUTION-FIBRE OPTIC CABLES	CAUTION-FUEL PIPE BELOW
RAW WATER MAIN BELOW	CAUTION-TELEPHONE CABLE BELOW
Caution: Sewer Below	CAUTION-STREET LIGHTING CABLE BELOW
CAUTION-FIRE MAINS BELOW	Other colours, texts and designs are available upon request subject to minimum order quantities and site of artwork.

The above texts are for illustration purposes and are not to scale. The colours, text design and mesh structure may vary from the above.



