



General

Emtelle PE Twinwall Duct is designed, manufactured and supplied within an Integrated Management System, incorporating internationally recognised Standards including ISO9001, ISO14001 & ISO18001.

The duct is designed to comply with ENATS 12-24 (Class 2) Industry Standard.

Duct systems are printed with standard markings, including any additional information required by the customer, to give durability and traceability after installation.

The duct is supplied on non-returnable wooden U-frames which are designed to be stored on even, stable ground; they must not be stored more than 3 high. Packaging should be recycled locally.

Standard length of a pipe is 3m or 6m.

Raw materials are Polyethylene. The external corrugated profile provides a stiff yet flexible & lightweight duct. The internal bore is smooth to ensure safe passage of the cable during installation.

Standard colour is Black; other colours are available upon request. Colour fastness and UV stability for UK and Ireland only, for 6 months external storage unless otherwise agreed by customer specification.

Duct Size

Nominal OD / ID	Class	No. Pipes / pallet	Quantity / pallet (3m lengths)	Quantity / pallet (6m lengths)
120mm / 100mm	2	81	243m	486m
150mm / 125mm	2	49	147m	294m
175mm / 150mm	2	36	108m	216m

- Each individual length comes with a factory fitted coupler as standard.
- A ring seal version providing a water tight system is available upon request.

Couplers

Couplers can be purchased individually if required, and are available in all sizes of duct.

These can be used to connect straight lengths of Twinwall.

Available in Black only.



THORNE &
DERRICK
INTERNATIONAL

Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com