



# 3M™ Medium Voltage EPDM Separable Connectors

Plug In Selection Guide.

Your Trusted Connection.



Voltage	Configuration	Cross section area mm <sup>2</sup>											Local Catalogue ID			
		25	35	50	70	95	120	150	185	240	300	400		500	630	
20/22(24)kV	Elbow 250A															93-EE 895-2 25-95
																93-EE 895-2 70-150
	Elbow 400A															93-EE 895-4 25-70
																93-EE 895-4 95-240

Voltage	Configuration	Cross section area mm <sup>2</sup>											Local Catalogue ID			
		25	35	50	70	95	120	150	185	240	300	400		500	630	
20/22(24)kV	Straight 250A															93-EE 890-2 25-95
																93-EE 890-2 70-150

Voltage	Configuration	Cross section area mm <sup>2</sup>											Local Catalogue ID			
		25	35	50	70	95	120	150	185	240	300	400		500	630	
20/22(24)kV	T 630A Asymmetrical															93-EE 995-6 25-70
																93-EE 995-6 95-240
																93-EE 995-6 240-400
	T 1250A Asymmetrical														93-EE 995-6 400-630	
20/22(24)kV	T 630A Symmetrical															93-EE 998-6 25-70
																93-EE 998-6 95-240

Voltage	Configuration	Cross section area mm <sup>2</sup>											Local Catalogue ID			
		25	35	50	70	95	120	150	185	240	300	400		500	630	
19/33(36)kV	Elbow 400A															94-EE 895-4 35-95
																94-EE 895-4 95-120
																94-EE 895-4 150-240

Voltage	Configuration	Cross section area mm <sup>2</sup>											Local Catalogue ID			
		25	35	50	70	95	120	150	185	240	300	400		500	630	
19/33(36)kV	T 630A Asymmetrical															94-EE 995-6 35-95
																94-EE 995-6 95-150
																94-EE 995-6 150-240
																94-EE 995-6 240-400
	T 1250A Asymmetrical														94-EE 995-6 400-630	



THORNE &  
DERRICK  
INTERNATIONAL

Thorne & Derrick  
+44 (0) 191 410 4292  
[www.powerandcables.com](http://www.powerandcables.com)

