

DSN DECONTACTOR is a compact and waterproof plug and socket-outlet with integral switch for industrial purposes.

DSN DECONTACTOR complies with the following regulations and standards(a):

European Directives Low Voltage and RoHS (affixing of CE marking), REACH European Regulation, standards IEC/EN 60309-1, IEC/EN 60309-4, IEC/EN 60947-3 (dealing with the load breaking capacities AC-22 and AC-23), UL 1682, UL 2682 (USA), CSA C22.2 N° 182.1-07 (Canada), MIL-S-901D (sea military specifications), GB/T 11918.1 (China).

DSN DECONTACTOR is certified by the following certification bodies:

LCIE (France), UL (USA), SAA (Australia), VDE (Germany), TR CU (Russia), CSA (Canada), Bureau Veritas Marine, MIL-S-901D (Military), CQC (China).



The use of DSN DECONTACTOR facilitates the compliance with:

- electrical machinery to the "Machinery" European Directive on isolating device, and to standard EN 60204-1 : Safety of machinery-electrical equipment of machines

- electrical installation:

\* to national regulations relating to the improvement of the safety and health of workers at work in France, Italy, Spain, Belgium,

\* to installation standards : IEC 60364 (international), HD 60364 (European), NFPA 70 (USA) and NF C 15-100 (French) or other national transposition of IEC/HD 60364.

### General information

	DSN1	DSN3	DSN6
(b) $I_n$	20 A	32 A	63 A
$U_{max}$ (V AC/V DC)	500/750	690/1 000	1 000/1 500
(c) Frequency (Hz)	≤ 500	≤ 500	≤ 500
(d) Number of contacts	4P+E	4P+E	4P+E
(e) Number of keying positions	23	24	24
Connection (min - max): mm <sup>2</sup>			
Flexible conductors (Cu): main contacts	1 - 2.5	2.5 - 6	6 - 16
Rigid/stranded conductors (Cu): main contacts	1.5 - 4	2.5 - 10	10 - 25
Tightening torque - main contacts	0.8 Nm	1.5 Nm	1.8 Nm
Wiring lugs	Option	Option	Option
Icc: conditional short circuit current (kA)			
with gG fuse	10 kA	10 kA	10 kA
with RK1 NTD fuse	100 kA	100 kA	100 kA

### Auxiliaries / pilots contacts

	DSN1	DSN3	DSN6
$I_n$	2 A	30 A	16 A
$U_{max}$ (V AC/V DC)	250 V	500 V	400 V
(f) Number of auxiliaries / pilots contacts	2 pil	2 aux	4 aux
Connection (min - max): mm <sup>2</sup>			
Flexible wiring	0.8	2.5 - 6	1 - 2.5
Rigid/stranded conductors:		2.5 - 10	1.5 - 4
Tightening torque		1.5 Nm	0.8 Nm

### Used as connector according to IEC/EN 61984: $I_n$

	DSN1	DSN3	DSN6
$I_n$	20 A	32 A	63 A
$U_{max}$	500 V AC 750 V DC	690 V AC 1000 V DC	1000 V AC 1500 V DC

### Breaking as plug and socket-outlet according to IEC/EN 60309-1

(g) $I_n$ (A) / $U_{max}$ (V AC)	DSN1	DSN3	DSN6
20 - 500	20 - 500	32 - 690	45 - 1 000 63 - 690

### Breaking as switch according to IEC/EN 60947-3

(g) Category AC-22A: $I_n$ (A) - $U_{max}$ (V AC)	DSN1	DSN3	DSN6
20 - 500	20 - 500	32 - 690	40 - 690
(g) Category AC-23A: $I_n$ (A) - $U_{max}$ (V AC)	DSN1	DSN3	DSN6
20 - 500	20 - 500	32 - 480	63 - 400

### Breaking as plug and socket-outlet according to UL 2682


Power: HP	DSN1	DSN3	DSN6
7.5	7.5	15	20

### Increase of DC load-breaking capacity (contacts in series)

	DSN1	DSN3	DSN6
Option	Option	Option	Option
Number of operations			
According to IEC/EN 60309-1 : Cos(Φ) 0,6	5 000	2 000	2 000
According to UL 2682 : Cos(Φ) 0,75	6 000	6 000	6 000

### Isolating distance

	DSN1	DSN3	DSN6
10 mm	10 mm	10 mm	14 mm




V : Contact spring

W : Arc chamber

X : Ejection spring


Y : Ejection ring



Contacts with silver nickel alloy tips (Ag/Ni : 85/15)



Spring assisted terminal:  
Stainless steel ring



Contacts in series

### Thermal features

	DSN1	DSN3	DSN6
Temperature of use mini/maxi (°C)	-40/+60 °C	-40/+60 °C	-40/+60 °C
Storage temperature mini/max: (°C)	-40/+80 °C	-40/+80 °C	-40/+80 °C
Maximal temperature rise (Kmax)	36 K	38 K	40 K
Time constant (to reach 63 % of Kmax)	17 mn	21 mn	22 mn

### Mechanical features

	DSN1	DSN3	DSN6
(h) IP: connected device		IP66/IP67/IP69	
IP: lid/cap closed		IP66/IP67/IP69	
IP: socket-outlet with lid/cap opened		IP4X - Safety shutter	
(i) IK	IK09	IK09	IK09
Retaining/releasing device		Red release button	
(j) Casing		GRP (poly)	
	Standard color	MARECHAL® Blue	
	Other colors	On request	
Vibrations resistance	✓	✓	✓
Resistance to chemical agents		Contact us	
Protection against UV (according to UL 746C or equivalent)	f1	f1	f1
Salt mist resistance	> 50 000 h	> 50 000 h	> 50 000 h
Screws and bolts		Stainless steel	
Weight of inlet without accessory (≈)	0.1 kg	0.1 kg	0.2 kg
Weight of socket-outlet without accessory (≈)	0.2 kg	0.3 kg	0.4 kg

### Main options

	DSN1	DSN3	DSN6
Socket-outlet opening up to 180°	Included	Included	Included
Self-returning lid	IP40	IP40	IP40
Inlet cap	IP66/IP67	IP66/IP67	IP66/IP67
Self-returning inlet lid		IP55	IP55
Locking / padlocking	✓	✓	✓
Automatic self-ejection	✓	✓	✓
Larger release button ("STOP")	✓	✓	✓
Finger draw plates	✓	✓	✓
Industrial-domestic adapter	✓	✓	

### Mounting accessories

	DSN1	DSN3	DSN6
Poly sleeve: angle (°)	30/70	30/70	30/70
Metal sleeve: angle (°)	0/30	0/30	0/30/70
Poly box: angle (°)	30	30	30
Metal box: angle (°)		20	20
Poly box + poly sleeve: angle (°)	70	70	70
Metal box + poly sleeve: angle (°)	30	30	30
Metal box + metal sleeve: angle (°)		0/30	0/30/70
Poly straight handle with built-in cable gland: range take (mm)	5 - 21	5 - 21	10 - 30
Threaded poly straight handle	M20 - M32	M20 - M40	M20 - M40
Threaded metal straight handle		M20 - M32	M20 - M40
Poly 60° handle with built-in cable gland: range take (mm)	9 - 18		
Poly straight handle + separated poly cable gland:	5 - 25	5 - 32	5 - 32
Metal straight handle + separated metal cable gland: range take (mm)		7 - 24	7 - 32

### Spare parts

	DSN1	DSN3	DSN6
Inlet or socket-outlet interior moulding	✓	✓	✓
Inlet or socket-outlet contacts	✓	✓	✓
Inlet or socket-outlet colored gasket	✓	✓	✓
Inlet or socket-outlet casing	✓	✓	✓
Socket-outlet casing gasket	✓	✓	✓

[Catalog: Web link](#)


[Click !](#)

[Click !](#)

[Click !](#)



### Dimensions




mm	DSN1	DSN3	DSN6
A	25	15	16
B	147	171	184
C	58	77	84
E	42	48	55

### Finger draw plate



Locking pin for 2 padlocks

### Poly straight handle with built-in cable gland



- (a) European Regulation REACH: registration, evaluation, authorisation and restriction of chemicals  
IEC/EN 60309-1 : "Plugs, socket-outlets and couplers for industrial purposes – Part 1: General requirements"  
IEC/EN 60309-4 : "Plugs, socket-outlets and couplers for industrial purposes – Part 4: Switched socket-outlets and connectors with or without interlock"  
IEC/EN 60947-3 : "Low-voltage switchgear and controlgear – Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units"  
IEC/EN 61984 : "Connectors – Safety requirements and tests"  
UL 1682 : "Plugs, Receptacles, and Cable Connectors of the Pin and Sleeve Type"  
UL 2682 : "Outline of Investigation for Switch-Rated Plugs and Receptacles"  
CSA C22,2 No 182,1-07 : "Plugs, Receptacles, and Cable Connectors of the Pin and Sleeve Type"  
MIL-S-901D : Military specifications critical mechanical impacts resistance for equipments mounted on ships  
GB/T 11918.1 : "Plugs, socket-outlets and couplers for industrial purposes – Part 1: General requirements"
- (b) In : Rated current as defined by the manufacturer
- (c) Other frequency: contact us
- (d) Contacts with silver-nickel tips (Ag/Ni 85/15)
- (e) Number of voltage / frequency / grid, keying positions
- (f) Auxiliaries contacts are located on the plug and socket-outlet sides. Pilot contacts are only located on the socket-outlet side.
- (g) For direct current applications : contact us
- (h) IP : Degrees of protection provided by enclosures (IEC/EN 60529)
- (i) IK : Degrees of protection provided by enclosures against mechanical impacts (IEC/EN 62262)
- (j) GRP : Glass-reinforced technical plastic